



IECEX Certificate of Conformity

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: IECEx UL 13.0086X

Issue No: 7

Certificate history:

Issue No. 7 (2019-07-31)

Issue No. 6 (2018-09-27)

Issue No. 5 (2016-10-31)

Issue No. 4 (2016-08-29)

Issue No. 3 (2015-03-18)

Issue No. 2 (2014-07-14)

Issue No. 1 (2014-03-27)

Issue No. 0 (2014-03-03)

Status: **Current**

Page 1 of 5

Date of Issue: **2019-07-31**

Applicant: **Derrick Mfg. Corporation**
590 Duke Road
Buffalo, NY 14225
United States of America

Equipment: **Flameproof Electric Vibrating Motors - EX, SGX, SG2X &, SG3X**

Optional accessory:

Type of Protection: **Flameproof "db"**

Marking:

Ex db IIB T3 Gb

-20°C to +40°C; -20°C to +55°C

*Approved for issue on behalf of the IECEx
Certification Body:*

Erin LaRocco

Position:

Staff Engineer

*Signature:
(for printed version)*

Date:

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting the [Official IECEx Website](http://www.iecex.com).

Certificate issued by:

UL LLC
333 Pfingsten Road
Northbrook IL 60062-2096
United States of America





IECEX Certificate of Conformity

Certificate No: IECEX UL 13.0086X

Issue No: 7

Date of Issue: 2019-07-31

Page 2 of 5

Manufacturer: **Derrick Mfg. Corporation**
590 Duke Road
Buffalo, NY 14225
United States of America

Additional Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2011 Explosive atmospheres - Part 0: General requirements
Edition:6.0

IEC 60079-1 : 2014-06 Explosive atmospheres - Part 1: Equipment protection by flameproof enclosures "d"
Edition:7.0

IEC 60079-31 : 2013 Explosive atmospheres - Part 31: Equipment dust ignition protection by enclosure "t"
Edition:2

*This Certificate **does not** indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.*

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

Test Report:

[US/UL/ExTR13.0098/07](#)

Quality Assessment Report:

[US/UL/QAR14.0003/04](#)



IECEX Certificate of Conformity

Certificate No: IECEx UL 13.0086X

Issue No: 7

Date of Issue: 2019-07-31

Page 3 of 5

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The series EX, SGX, SG2X and SG3X motors are totally enclosed non-ventilated industrial flameproof vibrating motors intended for continuous operation. They are provided with integral mounting pads and self-contained eccentric weights which cause the motor to produce the desired vibration of the equipment to which the motor is mounted.

Please see Annex for additional information.

SPECIFIC CONDITIONS OF USE: YES as shown below:

- Flameproof joints are other than those specified in Table 1 of IEC 60079-1. Contact Derrick for joint dimensions.
- Warning - To minimize the risk of electrostatic discharge, adequate grounding must be maintained.
- For motors for use with a frequency converter, use of the $145 \pm 5^{\circ}\text{C}$ thermostat is mandatory for appropriate direct thermal protection and marking of T3 temperature code.



IECEX Certificate of Conformity

Certificate No: IECEx UL 13.0086X

Issue No: 7

Date of Issue: 2019-07-31

Page 4 of 5

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Issue 1: Nomenclature and minor drawing changes not affecting the safety of the device.

Issue 2: Revisions to drawings not affecting the safety of the device.

Issue 3: Minor drawing corrections and additional cover bolts added.

Issue 4: Addition of variable frequency rating from 30 Hz through 60 Hz and revised IP rating from IP56 to IP66.

Issue 5: Minor drawing revisions. No construction changes made as a part of this revision.

Issue 6: Updated to the latest edition of IEC 60079-1 and drawing revisions.

Issue 7: Drawing revisions and alternate construction.



IECEX Certificate of Conformity

Certificate No: IECEX UL 13.0086X

Issue No: 7

Date of Issue: 2019-07-31

Page 5 of 5

Additional information:

Annex:

[Annex to IECEX UL 13.0086X Issue 7.pdf](#)



IECEx Certificate of Conformity

Certificate No.: IECEx UL 13.0086X

Issue No.: 7

Page 1 of 2

TYPE DESIGNATION

Nomenclature for type EX, SGX, SG2X and SG3X:

EX -230/460 -5 -003
I II III IV

I – Series Designation

EX - Ex series
SGX - SGX series
SG2X - SG2X series
SG3X – SG3X series

II – Supply Voltage Rating

-215/220 - 215/220 VAC
-230 – 215/220/230/240 VAC
-230/240 -230/240 VAC
-380/400 -380/400 VAC
-400 – 380/400/415 VAC
-415 - 415 VAC
-440 - 440 VAC
-460 – 440/460/480 VAC
-460/480 - 460/480 VAC
-500/525 – 500/525 VAC
-575/600 - 575/600 VAC
-690 - 690/700 VAC

III – Frequency Rating (50 Hz or 60 Hz or variable frequency)

-5 – 50 Hertz Sinusoidal Power or 30-60 Hz Constant Torque, Frequency Converter Use
-6 – 60 Hertz Sinusoidal Power or 30-60 Hz Constant Torque, Frequency Converter Use

IV - Certified Designation

-003 - ATEX Constant
-014 – NEC/ATEX/IECEx Constant

PARAMETERS RELATING TO THE SAFETY

215/220 VAC, 8.7 A Max
215/220/230/240 VAC, 8.7 A Max
230/240 VAC, 8.7 A Max
380/400 VAC, 8.7 A Max
380/400/415 VAC, 8.7 Max
415 VAC, 8.7 A Max
440 VAC, 8.7 A Max
440/460/480 VAC, 8.7 Max
460/480 VAC, 8.7 A Max
500/525 VAC, 8.7 A Max
575/600 VAC, 8.7 A Max
690/700 VAC, 8.7 A Max



IECEx Certificate of Conformity

Certificate No.: IECEx UL 13.0086X

Issue No.: 7

Page 2 of 2

MARKING

Marking has to be readable and indelible; it has to include the following indications:

+ DERRICK CORPORATION ISO 9001 : 2015 590 DUKE RD. BUFFALO, N.Y. 14225 U.S.A. +		DENKO 08ATEX0726988X CE 0539 II 2 G Ex db IIB T3 Gb IP66 IECEx U.L. 13.0086X Ex db IIB T3 Gb IP66	
Model Number Numéro de Modèle	Serial Number Numéro De Série	WEING DIAGRAM DIAGRAMME D'ENROULEMENT USE 80°C WIRE MIN.	
Speed Vitesse RPM	Temperature Rise Elevation de Température °C	Operating Temperature Code Code de Température en Service T3	1522-00-006
Voltage Tension	Power Pouvoir HP KW	Therml Switch Rating: Valeur d'Interrupteur Thermique PLDT DUTY 750 VA 115-250 VAC	Temperature Température °C AMB.
For Converter Supply Minimum Switching Frequency - 9 Hz PWM-Constant Torque - (30-60) Hz	Full Load Amps Courant Pleine Charge	Locked Rotor Code Code du rotor fermé à dé	Insulation Class Classe de l'isolation S.F. 1.0
Phase 3	Skewd Frequency Rating Hz	Idle Amps Courant deowatte	Duty Service CONT/S1
		Weight Kgs	Year Manufactured (+)

- MATERIAL: 304 SS x 0.018 THICK
- NOTES: 1) ALL DIMENSIONS TYP. U.O.N.
 2) PROTECTIVE PAPER
 3) HELVETICA RED BOLD TEXT

Installation Instructions

Before opening the enclosure in a flammable atmosphere the circuits must be interrupted.

The certification applies to equipment with and without cable glands and cables. All cable entry devices, elbows, and blanking elements shall be IECEx certified in type of explosion protection flameproof enclosure "db", suitable for the conditions of use and correctly installed.

Unused apertures shall be closed with IECEx certified suitable blanking elements.

Vibrators having IECEx Certification may be repaired only to the extent that the repair does not compromise the flameproof safety aspects of the enclosure. Consequently, repair is limited to parts external to the flameproof enclosure. All other repairs shall be performed at Derrick Corporation or a Derrick approved IECEx authorized repair facility.